

Serial No.10/625,240
Amendment dated June 16, 2006
Reply to Office Action dated March 16, 2006

JUN 16 2006**AMENDMENT TO THE CLAIMS**

1-22 (Cancelled)

23. (Currently Amended) A system comprising:

a memory to store IA-32 instructions;

an expanded logical register set including more than eight logical registers of a first type;

~~an~~ a bus coupled to said memory; and

IA-32 instruction set decoding logic coupled to the expanded logical register set and the memory via the ~~internal~~ bus,

wherein the IA-32 instruction set decoding logic is to determine whether a mod field of a ModR/M byte of an IA-32 instruction contains a predetermined value;

~~determine~~ whether an r/m field of the ModR/M byte of the IA-32 instruction contains a predetermined value;

~~determine~~ whether an index field of a scale index base (SIB) byte contains a predetermined value; and

decode an expanded logical register identifier.

24. (Previously Presented) The system of claim 23, wherein said expanded logical register set includes up to sixteen logical registers of a first type.

25. (Previously Presented) The system of claim 23, wherein said expanded logical register set includes up to thirty-two logical registers of a first type.

Serial No.10/625,240
Amendment dated June 16, 2006
Reply to Office Action dated March 16, 2006

26. (Previously Presented) The system of claim 23, wherein the more than eight logical registers of a first type include more than eight logical general integer registers.
27. (Previously Presented) The system of claim 23, wherein the more than eight logical registers of a first type include more than eight logical multimedia extension technology registers.
28. (Previously Presented) The system of claim 23, wherein the more than eight logical registers of a first type include more than eight logical SIMD (single instruction multiple data) floating-point registers.
29. (Previously Presented) The system of claim 23, further comprising:
expanded register set decoding logic, coupled to said IA-32 instruction set decoding logic, to determine whether an instruction includes an at least four-bit register identifier, the at least four-bit register identifier to specify one logical register of said expanded logical register set.
30. (Previously Presented) The system of claim 29, wherein said expanded register set decoding logic is to decode an at least four-bit identifier.
31. (Previously Presented) The system of claim 30, wherein said expanded register set decoding logic is to decode the at least four-bit register based at least in part on at least four bits

Serial No. 10/625,240
Amendment dated June 16, 2006
Reply to Office Action dated March 16, 2006

of a scale index base (SIB) byte of the instruction.

32. (Previously Presented) The system of claim 31, wherein said expanded register set decoding logic is to decode the at least four-bit register based at least in part on at least one bit of a scale field of the scale index base (SIB) byte of the instruction.

33. (Previously Presented) The system of claim 29, wherein said expanded register set decoding logic is to decode an at least five-bit register identifier.

34. (Previously Presented) The system of claim 33, said expanded register set decoding logic is to decode the at least five-bit register based at least in part on five bits of a scale index base (SIB) byte of the instruction.

35. (Previously Presented) The system of claim 34, wherein said expanded register set decoding logic is to decode the at least five-bit register based at least in part on two bits of a scale field of the scale index base (SIB) byte of the instruction.

36. (Currently Amended) A set of instructions residing in a computer readable storage medium, said set of instructions capable of being executed by a storage controller to implement a method for processing data, the method comprising:

determining whether a mod field of a ModR/M byte of an IA-32 instruction contains a value selected from the values of 01B, 10B and 00B;

determining whether an r/m field of the ModR/M byte of the IA-32 instruction contains a

Serial No.10/625,240
Amendment dated June 16, 2006
Reply to Office Action dated March 16, 2006

value of 100B;

determining whether an index field of a scale index base (SIB) byte contains a value of 100B; and

decoding an at least four-bit logical register identifier.

37. (Previously Presented) The set of instructions of claim 36, wherein decoding the at least four-bit logical register identifier is based at least in part on at least one bit of a scale field of a scale index base (SIB) byte of the IA-32 instruction.

38. (Previously Presented) The set of instructions of claim 36, wherein the at least four-bit logical register identifier is an at least five-bit logical register identifier.

39. (Previously Presented) The set of instructions of claim 38, wherein decoding an at least five-bit logical register identifier is based at least in part on two bits of a scale field of a scale index base (SIB) byte of the IA-32 instruction.

40. (Previously Presented) A processor comprising:
a logical register set including more than eight logical registers of a first type;
instruction decoding logic coupled to the logical register set, said instruction decoding logic including:

a first comparator to determine whether a mod field of a ModR/M byte of an IA-32 instruction contains a value selected from the values of 01B, 10B, and 00B;

a second comparator to determine whether an r/m field of the ModR/M byte of

Serial No.10/625,240
Amendment dated June 16, 2006
Reply to Office Action dated March 16, 2006

the IA-32 instruction contains a value of 100B;

a third comparator to determine whether an index field of a scale index base (SIB)

byte contains a value of 100B; and

a decoder to decode an at least four-bit logical register identifier.

41. (Previously Presented) The processor of claim 40, wherein the decoder to decode an at least four-bit logical register identifier is to decode the at least four-bit logical register identifier based at least in part on at least one bit of a scale field of a scale index base (SIB) byte of the IA-32 instruction.